Expulsion fuse-link, medium voltage, 40 A, AC 15 kV, 533 mm, ANSI, T slow $\,$



15TB40

General specifications	
Product name	Eaton Bussmann series medium voltage expulsion fuse
Part no.	15TB40
EAN	5027590435963
Product Length/Depth	225 millimetre
Product height	76 millimetre
Product width	106 millimetre
Product weight	42.88 gram
Compliances	Contact Manufacturer
Certifications	ANSI/IEEE Std C37.42
Product Tradename	None
Product Type	Medium voltage expulsion fuse
Product Sub Type	None
Electrical data	
Amperage Rating	40 A
Voltage rating	15 kV
Current characteristic type	Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics
Rated frequency - min	50 Hz
Rated frequency - max	60 Hz
Product specifications	
Application	Primary side transformer protection, feeder protection, capacitor bank protection
Standard	ANSI
Type of termination	Fixed buttonhead

Technical data ETIM 9.0

lecinical data ETHVI 5.0				
Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)				
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Expulsion fuse-link, medium voltage (ecl@ss13-27-14-21-28 [AGH830004])				
Rated current	Α	40		
Rated voltage	kV	15		
Voltage type		AC		
Rated frequency	Hz	50 - 60		
Release characteristic		Т		
Type of termination		Fixed buttonhead		
Standard		ANSI		