



**Undervoltage relays, Un x 0, 85, 230/400 VAC, 2W**

**Part no. REUVM2**  
**Catalog No. 167284**

Similar to illustration

### Design verification as per IEC/EN 61439

Technical data for design verification				
Rated operational current for specified heat dissipation	$I_n$	A		5
Heat dissipation per pole, current-dependent	$P_{vid}$	W		1.2
Equipment heat dissipation, current-dependent	$P_{vid}$	W		3.4
Static heat dissipation, non-current-dependent	$P_{vs}$	W		1
Operating ambient temperature min.		°C		-25
Operating ambient temperature max.		°C		60
				0

### Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Under voltage monitoring relay for distribution board (EC001667)				
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Under voltage monitoring relay for distribution board (ecl@ss10.0.1-27-14-23-27 [ACN373011])				
Rated voltage		V		400
Rated frequency		Hz		50 - 50
Indicated measuring range				3N, 400/230V
Max. switching power		VA		1250
Release delay		ms		500
Max. electrical switching cycles		c/min		6
Voltage type				AC
Mounting method				DIN rail
Width in number of modular spacings				1
Built-in height		mm		90
Degree of protection (IP)				IP20