

Keypad with OLED display for DE1, DC1, DA1, DB1, RASP5, RAM05



Part no. DX-KEY-OLED
169133
EL Number 4137450
(Norway)

General specifications		
Product name		Eaton DX Keypad
Part no.		DX-KEY-OLED
EAN		4015081656127
Product Length/Depth		16 millimetre
Product height		90 millimetre
Product width		110 millimetre
Product weight		0.1 kilogram
Certifications		UL Category Control No.: NMMS, NMMS7 IEC/EN61800-5 CSA-C22.2 No. 14 IEC/EN61800-3 UL report applies to both US and Canada CE UL 508C Certified by UL for use in Canada UL UL File No.: E172143
Product Tradename		DX
Product Type		Accessory
Product Sub Type		Keypad
Features & Functions		
Features		Multilingual
Fitted with:		Plug-in connection cable (approx 3 m, RJ45, 8-pin) OLED display
General information		
Accessory/spare part type		Control panel
Degree of protection (front side)		IP54
Degree of protection		IP00
Product Category		Accessories
Suitable for		Branch circuits, (UL/CSA)
Used with		DA1, DB1, DC1, DE1, RAM05, RASP5
Climatic environmental conditions		
Ambient operating temperature - max		50 °C
Ambient operating temperature - min		-10 °C
Design verification		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for frequency controller (EC002025)			
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter (accessories) (ecl@ss13-27-02-31-92 [AFR303008])			
Type of accessory/spare part			Control panel
Accessory			Yes
Spare part			No