

Surge arrester plug-in unit, 280VAC, 1p

Part no. SPDT3-280
170484
EL Number 1609785
(Norway)

General specifications		
Product name		Eaton Moeller series xPole - SPDT3 Surge Protection Device
Part no.		SPDT3-280
EAN		4015081669820
Product Length/Depth		52 millimetre
Product height		60 millimetre
Product width		17.5 millimetre
Product weight		0.044 kilogram
Compliances		RoHS conform
Product Tradename		xPole - SPDT3
Product Type		Surge Protection Device
Product Sub Type		None
Delivery program		
Application		Open areas Residential buildings Utility buildings
Type		Surge arrester
Technical Data - Electrical		
Voltage protection level		1.4 kV
Voltage protection level (L-N)		0 kV
Voltage protection level (N-PE)		0 kV
Nominal voltage at AC		280 V
Nominal voltage at DC		0 V
Continuous voltage at AC - max		280 V
Continuous voltage at DC - max		0 V
PV-voltage - max		0 V
Nominal discharge surge current (8/20)		5 kA
Discharge surge current (8/20) - max		10 kA
Short-circuit breaking capacity (ISCCR)		0 kA
Signalling at the device		Optic
Technical Data - Mechanical		
Frame		1 modular spacing
Mounting method		On basic element
Number of conductors without earthing		0
Conductor cross section (flexible, fine-strand) - min		0 mm ²
Conductor cross section (flexible, fine-strand) - max		0 mm ²
Conductor cross section (solid, solid-strand) - min		25 mm ²
Conductor cross section (solid, solid-strand) - max		25 mm ²
Degree of protection		IP20
Additional information		
System configuration type		Other

Technical data ETIM 9.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Internal and external lightning protection / Lightning protection (other) / Lightning protection (other, not specified) (ecl@ss13-27-17-90-90 [AHE465002])		
System configuration DC		No
System configuration IT		No
System configuration TN		No
System configuration TN-C		No

System configuration TN-C-S		No
System configuration TN-S		No
System configuration TT		No
System configuration other		Yes
Number of conductors (without earthing)		0
Nominal discharge surge current (8/20)	kA	5
Max. discharge surge current (8/20)	kA	10
Nominal voltage AC	V	280
Nominal voltage DC	V	0
Max. continuous voltage AC	V	280
Max. continuous voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	1.4
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Max. overcurrent protection device, parallel connection (fuse)	A	0
Max. overcurrent protection device, series connection (fuse)	A	125
Short-circuit breaking capacity (I _{sc})	kA	0
Integrated short-circuit protection		No
Integrated short-circuit protection selective to fuse gG	A	0
Integrated backup fuse		No
Leakage-current free		No
Mounting method		On basic element
Construction size		1 modular spacing
Max. conductor cross section solid (solid, stranded)	mm ²	25
Max. conductor cross section flexible (fine-strand)	mm ²	0
With remote signalling contact		No
Signalling at the device		Optical
Category type 2		No
Degree of protection (IP)		IP20