



Fuse-link, high speed, 16 A, AC 660 V, 200 kA, size 0000, 18 x 19 x 80 mm, gR, UL



Part no. FUSE 16A 660V 0000FU/65 GR UR
Catalog No. 170M0209

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	16
Rated voltage			AC 660 V
Construction size			size 0000
Size			18 x 19 x 80 mm
Utilization category			gR
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			UL
Shape			square body with offset bolted tags
Standards/Regulations			UL 248-13

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	16
Rated voltage		V	660
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			gR (general purpose semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusssmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf
-------------------------	---