



Fuse-link, high speed, 100 A, AC 690 V, 200 kA, DIN 00, aR, DIN, IEC, type T indicator, live gripping lugs



Part no. **FUSE 100A 690V 00TN/80 AR UR**  
 Catalog No. **170M2664**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	100
Rated voltage			AC 690 V
Construction size			DIN 00
Utilization category			aR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with offset bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	100
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

High-speed full-line catalogue (pdf)	<a href="http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf">http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf</a>
--------------------------------------	---