



Fuse-link, high speed, 550 A, AC 690 V, size 1, 53 x 69 x 51 mm, aR, UL, IEC, 18 UNC, square body with flush end contacts



Part no. **FUSE 550A 690V 1GN/50 AR UC**
 Catalog No. **170M4515**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	550
Rated voltage			AC 690 V
Construction size			size 1
Size			53 x 69 x 51 mm
Utilization category			aR
Status indicator			single indicator
Description			18 UNC
Standard/Approval			UL IEC
Shape			square body with flush end contacts

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	550
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No