

**Variable speed starter, Rated operational voltage 230 V AC, 1-phase, Ie 2.3 A, 0.37 kW, 0.5 HP, Radio interference suppression filter**



Powering Business Worldwide™

**Part no. DE1-122D3FN-N20N**

**174328**

**EL Number**

**4110092**

**(Norway)**

| General specifications        |  |
|-------------------------------|--|
| Product name                  | Eaton DE1 Variable speed starter   |
| Part no.                      | DE1-122D3FN-N20N   |
| EAN                           | 4015081707904  |
| Product Length/Depth          | 169 millimetre   |
| Product height                | 230 millimetre   |
| Product width                 | 45 millimetre  |
| Product weight                | 1.04 kilogram  |
| Certifications                | UL report applies to both US and Canada<br>CE<br>IEC/EN 61800-3<br>Certified by UL for use in Canada<br>CSA-C22.2 No. 14<br>UL Category Control No.: NMMS, NMMS7<br>IEC/EN61800-5<br>CUL<br>UL<br>Specification for general requirements: IEC/EN 61800-2<br>UL File No.: E172143<br>RoHS, ISO 9001<br>IEC/EN61800-3<br>Safety requirements: IEC/EN 61800-5-1<br>RCM<br>UL 508C |
| Product Tradename             | DE1  |
| Product Type                  | Variable speed starter   |
| Product Sub Type              | None   |
| Catalog Notes                 | Overload cycle for 60 s every 600 s  |
| Features & Functions          |  |
| Features                      | Parameterization: drivesConnect<br>Parameterization: drivesConnect mobile (App)<br>Parameterization: Fieldbus<br>Parameterization: Keypad  |
| Fitted with:                  | PC connection<br>Radio interference suppression filter   |
| General information           |  |
| Cable length                  | C1 ≤ 5 m, Radio interference level, maximum motor cable length<br>C3 ≤ 25 m, Radio interference level, maximum motor cable length<br>C2 ≤ 10 m, Radio interference level, maximum motor cable length   |
| Communication interface       | Modbus RTU, built in<br>OP-Bus (RS485), built in   |
| Connection to SmartWire-DT    | Yes<br>In conjunction with DX-NET-SWD3 SmartWire DT module   |
| Degree of protection          | IP20<br>NEMA Other   |
| Electromagnetic compatibility | 1st and 2nd environments (according to EN 61800-3)   |
| Frame size                    | FS1  |
| Product category              | Variable speed starter   |
| Protection                    | Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)  |
| Protocol                      | MODBUS<br>EtherNet/IP<br>Other bus systems   |
| Radio interference class      | C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.<br>C1: for conducted emissions only<br>Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments                                  |
| Shock resistance              | 15 g, Mechanical, According to IEC/EN 60068-2-27, 11 ms  |
| Suitable for                  | Branch circuits, (UL/CSA)  |

|  |  |  |
|--|--|--|
| Vibration  |  | Resistance: According to EN 61800-5-1  |
| <b>Climatic environmental conditions</b>                       |  |  |
| Altitude   |  | Max. 2000 m<br>Above 1000 m with 1 % derating per 100 m  |
| Ambient operating temperature - min                            |  | -10 °C   |
| Ambient operating temperature - max                            |  | 60 °C  |
| Ambient operating temperature at 150% overload - min           |  | -10 °C   |
| Ambient operating temperature at 150% overload - max           |  | 60 °C  |
| Ambient storage temperature - min                              |  | -40 °C   |
| Ambient storage temperature - max                              |  | 70 °C  |
| Climatic proofing  |  | < 95 average relative humidity (RH), no condensation, no corrosion   |
| <b>Main circuit</b>  |  |  |
| Heat dissipation at current/speed                              |  | 10 W at 50% current and 0% speed<br>10.4 W at 50% current and 90% speed<br>11.6 W at 50% current and 50% speed<br>16.8 W at 100% current and 0% speed<br>16.8 W at 100% current and 50% speed<br>18.3 W at 100% current and 90% speed<br>5.6 W at 25% current and 0% speed<br>5.6 W at 25% current and 50% speed |
| Input current ILN at 150% overload                             |  | 6.2 A  |
| Leakage current at ground IPE - max                            |  | < 3.5 mA (AC-operated)<br>< 10 mA (DC-operated)  |
| Mains switch-on frequency                                      |  | Maximum of one time every 30 seconds   |
| Mains voltage - min  |  | 200 V  |
| Mains voltage - max  |  | 240 V  |
| Operating mode   |  | Speed control with slip compensation<br>U/f control  |
| Output frequency - min   |  | 0 Hz   |
| Output frequency - max   |  | 300 Hz   |
| Output voltage (U2)  |  | 230 V AC, 3-phase<br>240 V AC, 3-phase   |
| Overload current IL at 150% overload                           |  | 3.45 A   |
| Rated control supply voltage                                   |  | 10 V DC (Us, max. 0.2 mA)  |
| Rated frequency - min  |  | 45 Hz  |
| Rated frequency - max  |  | 66 Hz  |
| Rated operational current (Ie)                                 |  | 2.3 A at 150% overload (at an operating frequency of 16 kHz and an ambient air temperature of +50 °C)  |
| Rated operational power at 220/230 V, 50 Hz, 1-phase           |  | 0.37 kW  |
| Rated operational voltage                                      |  | 230 V AC, 1-phase<br>240 V AC, 1-phase   |
| Resolution   |  | 0.025 Hz (Frequency resolution, setpoint value)  |
| Short-circuit protection rating                                |  | 10 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring  |
| Starting current - max   |  | 200 %, IH, max. starting current (High Overload), For 1.875 seconds every 600 seconds, Power section   |
| Supply frequency   |  | 50/60 Hz   |
| Switching frequency  |  | 16 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit   |
| Voltage rating - max   |  | 240 V  |
| <b>Motor rating</b>  |  |  |
| Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload |  | 2.2 A  |
| Assigned motor current IM at 230 V, 50 Hz, 150% overload       |  | 2 A  |
| Assigned motor current IM at 400 V, 50 Hz, 150% overload       |  | 2 A  |
| Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload |  | 2.2 A  |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase              |  | 0.5 HP   |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase              |  | 0.5 HP   |
| <b>Apparent power</b>  |  |  |
| Apparent power at 230 V  |  | 0.92 kV-A  |
| Apparent power at 240 V  |  | 0.96 kV-A  |
| <b>Braking function</b>  |  |  |
| Braking torque   |  | Max. 30 % MN, Standard - Main circuit  |

|  |  |  |
|--|--|--|
|  |  | Adjustable to 100 %, DC - Main circuit   |
| <b>Control circuit</b>   |  |  |
| Number of inputs (analog)  |  | 1 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)  |
| Number of inputs (digital)   |  | 4 (parameterizable, 10 - 30 V DC)  |
| Number of outputs (analog)   |  | 0  |
| Number of outputs (digital)  |  | 0  |
| Number of relay outputs  |  | 1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))   |
| <b>Design verification</b>   |  |  |
| Equipment heat dissipation, current-dependent P <sub>vid</sub>                   |  | 20 W   |
| Heat dissipation capacity P <sub>diss</sub>                                      |  | 0 W  |
| Heat dissipation per pole, current-dependent P <sub>vid</sub>                    |  | 0 W  |
| Rated operational current for specified heat dissipation (I <sub>n</sub> )       |  | 2.3 A  |
| Static heat dissipation, non-current-dependent P <sub>vs</sub>                   |  | 0 W  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 9.0

|  |    |           |
|--|----|-----------|
| Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)  |    |           |
| Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency / Servo converter = < 1 kV (ecl@ss13-27-02-31-01 [AKE177019]) |    |           |
| Mains voltage  | V  | 200 - 240 |
| Mains frequency  |    | 50/60 Hz  |
| Number of phases input   |    | 1         |
| Number of phases output  |    | 3         |
| Max. output frequency  | Hz | 300       |
| Max. output voltage  | V  | 250       |
| Nominal output current I <sub>2N</sub>   | A  | 2.3       |
| Max. output at quadratic load at rated output voltage  | kW | 0.37      |
| Max. output at linear load at rated output voltage   | kW | 0.37      |
| Power consumption  | W  | 20        |
| Relative symmetric net frequency tolerance   | %  | 10        |
| Relative symmetric net voltage tolerance   | %  | 10        |
| Number of analogue outputs   |    | 0         |
| Number of analogue inputs  |    | 1         |
| Number of digital outputs  |    | 0         |

|  |  |    |             |
|--|--|----|-------------|
| Number of digital inputs                               |  |    | 4           |
| With control element                                   |  |    | No          |
| Application in industrial area permitted               |  |    | Yes         |
| Application in domestic- and commercial area permitted |  |    | Yes         |
| Supporting protocol for TCP/IP                         |  |    | No          |
| Supporting protocol for PROFIBUS                       |  |    | No          |
| Supporting protocol for CAN                            |  |    | No          |
| Supporting protocol for INTERBUS                       |  |    | No          |
| Supporting protocol for ASI                            |  |    | No          |
| Supporting protocol for KNX                            |  |    | No          |
| Supporting protocol for Modbus                         |  |    | Yes         |
| Supporting protocol for Data-Highway                   |  |    | No          |
| Supporting protocol for DeviceNet                      |  |    | No          |
| Supporting protocol for SUCONET                        |  |    | No          |
| Supporting protocol for LON                            |  |    | No          |
| Supporting protocol for PROFINET IO                    |  |    | No          |
| Supporting protocol for PROFINET CBA                   |  |    | No          |
| Supporting protocol for SERCOS                         |  |    | No          |
| Supporting protocol for Foundation Fieldbus            |  |    | No          |
| Supporting protocol for EtherNet/IP                    |  |    | Yes         |
| Supporting protocol for AS-Interface Safety at Work    |  |    | No          |
| Supporting protocol for DeviceNet Safety               |  |    | No          |
| Supporting protocol for INTERBUS-Safety                |  |    | No          |
| Supporting protocol for PROFI-safe                     |  |    | No          |
| Supporting protocol for SafetyBUS p                    |  |    | No          |
| Supporting protocol for BACnet                         |  |    | No          |
| Supporting protocol for other bus systems              |  |    | Yes         |
| Number of HW-interfaces industrial Ethernet            |  |    | 0           |
| Number of interfaces PROFINET                          |  |    | 0           |
| Number of HW-interfaces RS-232                         |  |    | 0           |
| Number of HW-interfaces RS-422                         |  |    | 0           |
| Number of HW-interfaces RS-485                         |  |    | 1           |
| Number of HW-interfaces serial TTY                     |  |    | 0           |
| Number of HW-interfaces USB                            |  |    | 0           |
| Number of HW-interfaces parallel                       |  |    | 0           |
| Number of HW-interfaces other                          |  |    | 0           |
| With optical interface                                 |  |    | No          |
| With PC connection                                     |  |    | Yes         |
| Integrated breaking resistance                         |  |    | No          |
| 4-quadrant operation possible                          |  |    | No          |
| Type of converter                                      |  |    | U converter |
| Degree of protection (IP)                              |  |    | IP20        |
| Degree of protection (NEMA)                            |  |    | Other       |
| Height   |  | mm | 230         |
| Width  |  | mm | 45          |
| Depth  |  | mm | 169         |