

Surge arrester, pluggable, 600V DC, 2p+PE

Part no. **SPPVT2H-06-2+PE**
176094

General specifications		
Product name		Eaton Moeller series xPole - SPPVT2.12 Surge Protection Device
Part no.		SPPVT2H-06-2+PE
EAN		4015081712908
Product Length/Depth		90 millimetre
Product height		65.5 millimetre
Product width		53.4 millimetre
Product weight		0.303 kilogram
Compliances		CE Marked RoHS conform
Product Tradename		xPole - SPPVT2.12
Product Type		Surge Protection Device
Product Sub Type		None
Delivery program		
Application		Open areas Residential buildings Utility buildings
Type		DC overvoltage protection Surge arrester
Technical Data - Electrical		
Connection		For ungrounded systems
Voltage rating (Iu) - max		600 V
Voltage protection level		2.7 kV
Voltage protection level (L-N)		0 kV
Voltage protection level (N-PE)		0 kV
Nominal voltage at AC		0 V
Nominal voltage at DC		600 V
Continuous voltage at AC - max		0 V
Continuous voltage at DC - max		800 V
PV-voltage - max		800 V
Nominal discharge surge current (8/20)		15 kA
Signalling at the device		Optic
Technical Data - Mechanical		
Frame		3 modular spacing
Mounting method		DIN rail (top hat rail) 35 mm
Conductor cross section (flexible, fine-strand) - min		25 mm ²
Conductor cross section (flexible, fine-strand) - max		25 mm ²
Conductor cross section (solid, solid-strand) - min		35 mm ²
Conductor cross section (solid, solid-strand) - max		35 mm ²
Degree of protection		IP20
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (In)		0 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		0 W
Static heat dissipation, non-current-dependent		0.02 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-40 °C
Ambient operating temperature - max		80 °C
Additional information		
Features		Category type 2
Special features		Pluggable

System configuration type	IT
---------------------------	----

Technical data ETIM 8.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss10.0.1-27-13-08-05 [ACN278011])			
System configuration DC			No
System configuration IT			Yes
System configuration TN			No
System configuration TN-C			No
System configuration TN-C-S			No
System configuration TN-S			No
System configuration TT			No
System configuration other			No
Number of conductors (without earthing)			
Nominal discharge surge current (8/20)		kA	15
Max. discharge surge current (8/20)		kA	
Nominal voltage AC		V	0
Nominal voltage DC		V	600
Max. continuous voltage AC		V	0
Max. continuous voltage DC		V	800
Max. PV-voltage		V	800
Voltage protection level		kV	2.7
Voltage protection level L-N		kV	0
Voltage protection level N-PE		kV	0
Max. overcurrent protection device, parallel connection (fuse)		A	
Max. overcurrent protection device, series connection (fuse)		A	
Short-circuit breaking capacity (I _{scbr})		kA	
Integrated short-circuit protection			No
Integrated short-circuit protection selective to fuse gG		A	
Integrated backup fuse			No
Leakage-current free			No
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			3 modular spacing
Max. conductor cross section solid (solid, stranded)		mm ²	35
Max. conductor cross section flexible (fine-strand)		mm ²	25
With remote signalling contact			No
Signalling at the device			Optic
Category type 2			Yes
Degree of protection (IP)			IP20