

Auxiliary contact, SmartWire-DT

Part no. **MCB-HK-SWD**
177175
EL Number **1666609**
(Norway)

General specifications

Product name	Eaton Distribution parts
Part no.	MCB-HK-SWD
EAN	4015081716197
Product Length/Depth	88.3 millimetre
Product height	74.7 millimetre
Product width	29.9 millimetre
Product weight	0.04 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accessory/spare part type	SWD interface module
Additional equipment required	Signaling switch
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for industrial and advanced commercial applications
Assembly width	1
Device fitting	Universal
EL number	1666609
Functions	Auxiliary switch
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0
Number of poles at main contact unit - max	0
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	15 V
Rated switch current	0.0263 A
Suitable for current of main contact unit - max	0 A
Type	Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker Accessory for residual current circuit breaker
Used with	SWD interface module Accessory Accessory for miniature circuit breaker Accessory for residual current circuit breaker Accessory for combined residual current/power circuit breaker
Voltage type	DC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Universal
Function		Auxiliary switch
Width in number of modular spacings		1

Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	0.0263
Rated voltage	V	15
Voltage type		DC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		0
Suitable for max. current main contact unit	A	0