

Connection cable; 6p; AC; coupling M12 flat; open end; L=5m



Part no. CSAS6A6CY2205
177307

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series CSAS Accessory Connection cable |
| Part no. | | CSAS6A6CY2205 |
| EAN | | 4015081717606 |
| Product Length/Depth | | 250 millimetre |
| Product height | | 25 millimetre |
| Product width | | 175 millimetre |
| Product weight | | 0.216 kilogram |
| Compliances | | CE |
| Product Tradename | | CSAS |
| Product Type | | Accessory |
| Product Sub Type | | Connection cable |
| Product Specification Details | | |
| Ambient operating temperature - max | | 70 °C |
| Ambient operating temperature - min | | -25 °C |
| Cable length | | 5 m |
| Cable sheath material | | Other |
| Cable type | | Multi-core Cable end, open, Output side Coupling, straight, Input side |
| Color cable sheath | | Yellow |
| Contact body material | | Other |
| Contact surface material | | Other |
| Continuity resistor | | 0 mΩ |
| Degree of protection | | Other |
| Electrical connection type (box-sided) | | Other |
| Electrical connection type (field-sided) | | M12 |
| Nominal current | | 0 A |
| Number Of Poles | | Six-pole |
| Permitted temperature of outer cable (assembled) without vibration - max | | 70 °C |
| Permitted temperature of outer cable (assembled) without vibration - min | | 40 °C |
| Permitted temperature of outer cable (assembling/handling) - max | | 70 °C |
| Permitted temperature of outer cable (assembling/handling) - min | | 40 °C |
| Plug-in contact type (field-sided) | | Female (bus) |
| Positioning cable feed (box-sided) | | Other |
| Positioning cable feed (field-sided) | | Straight |
| Product category | | Accessories |
| Rated operational voltage (Ue) - max | | 0 V |
| Voltage type | | DC |

Technical data ETIM 9.0

| Sensors (EG000026) / Sensor-actuator patch cord (EC001855) | | |
|--|--|--------------|
| Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor/actuator adapter, with cable (ecl@ss13-27-06-03-13 [AFR625008]) | | |
| Number of poles | | 6 |
| Type of electrical connection, field-sided | | M12 |
| Type of plug-in contact, field sided | | Female (bus) |
| Positioning cable feed, field-sided | | Straight |
| Type of electrical connection, box-sided | | Other |
| Type of plug-in contact, box-sided | | |

| | | | |
|--|----|--|------------|
| Positioning cable feed, box-sided | | | Other |
| Cable length | m | | 5 |
| Material of cable sheath | | | Other |
| Halogen free | | | No |
| Colour cable sheath | | | Yellow |
| With LED indication | | | No |
| Screened | | | No |
| Cable type | | | Multi-core |
| Vulcanize | | | No |
| Material contact body | | | Other |
| Material of contact surface | | | Other |
| Permitted cable outer temperature after assembling without vibration | °C | | 40 - 70 |
| Permitted cable outer temperature during assembling/handling | °C | | 40 - 70 |
| Rated current I _n | A | | 0 |
| Rated voltage | V | | 0 |
| Continuity resistance | mΩ | | 0 |
| Degree of protection (IP) | | | Other |