



Connection 3p horizontal



Powering Business Worldwide™

Part no. IZMX-TH403-4000-1  
 Catalog No. 183976  
 Alternate Catalog No. 65A3137G11  
 EL-Nummer (Norway) 0004398386

Delivery program

|                                      |       |   |   |
|--------------------------------------|-------|---|---|
| Product range                        |       |   | Accessories   |
| Accessories                          |       |   | Main terminal kits  |
| Accessories                          |       |   | Horizontal connections  |
|                                      |       |   | This connector kit includes T-shaped adapters for the inner main terminals and L-shaped adapters for the outer main terminals. The L shape makes it possible to move the pole centers outwards, allowing for bars of up to 120 mm to be connected. This connector kit is only intended for the 4,000 A horizontal terminal. |
| Rated current                        | $I_n$ | A | 4000  |
| Pole                                 |       |   | 3   |
| For use with                         |       |   | IZMX40...3...40F<br>IZMX40...3...40W<br>INX40...3...40F<br>INX40...3...40W  |
| Information about equipment supplied |       |   | Main terminals are not supplied as standard with the basic devices and cassettes. Each set includes the connections for top and bottom. 3-pole= 6 connections; 4-pole= 8 connections, including accessories for mounting on the flanged circuit-breaker connection.   |

Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

Technical data ETIM 7.0

|   |  |  |   |
|---|--|--|---|
| Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)  |  |  |   |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ec@ss10.0.1-27-37-13-05 [ACN990012]) |  |  |   |
| Suitable for number of poles  |  |  | 3 |

## Dimensions

