



Signalling switch ready to switch on, 1W (IZMX-SR)

**Part no.** IZMX-LCS-SR-1  
**Catalog No.** 184106  
**Alternate Catalog No.** 67C2814G31

### Delivery program

Product range		Accessories
Accessories		Auxiliary contact
Accessories		Operational readiness indicator with plug for direction connection to spring release
		Automatic closing after readiness for operation. Can only be used together with a closing release
For use with		IZMX16..., IZMX40... INX16..., INX40...
Instructions		Can be used with IZMX16(40)-SR... closing release for automatic closing upon availability
		1 changeover contact

### Technical data

#### Rated breaking capacity

Inductive load		
250 V AC	A	10
125 V DC	A	0.5
250 V DC	A	0.25

### Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ec@ss10.0.1-27-37-13-02 [AKN342013])		
Number of contacts as change-over contact		1
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of fault-signal switches		
Rated operation current I <sub>e</sub> at AC-15, 230 V	A	10
Type of electric connection		Flat plug-in connection
Model		Integrable
Mounting method		Other
Lamp holder		