DATASHEET - BPZ-GND-800

Earth bar (copper) 20x5mm, insulated on mounting plate, for housing width 800mm



Part no.	BPZ-GND-800
	187869
EL Number	2456446
(Norway)	

General specifications

Functions	Additional equipment
Features	Insulated mounting
Additional information	
Suitable for width	800 mm
Thickness	5 mm
Rail length	408 mm
Housing material	Copper Sheet steel
Clearance from back plate	29 mm
Tightening torque - max	0 N·m
Connection size, connection facility	Other
Number of connections	6
Material	Copper
Mounting position	Horizontal
Mounting method	Other Surface mounting Floor standing distribution board Horizontal
Surface of the contact rail	Untreated
Surface finishing	Galvanized
Fechnical Data - Mechanical	
Number of poles	Single-pole
Amperage rating	274 A
Туре	Additional equipment
Delivery program	
Product Sub Type	Other
Product Type	Accessories
Product Tradename	xEnergy Basic
Compliances	RoHS conform
Product weight	2.4 kilogram
Product width	688 millimetre
Product height	30 millimetre
Product Length/Depth	80 millimetre
EAN	4015081855544
Part no.	BPZ-GND-800
Product name	Eaton xEnergy Basic other accessory

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Earthing rail for distribution board (EC000329)

Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Earthing rail for distribution board (ecl@ss13-27-40-06-05 [AC0373016]) Number of connections 6 274 Rated current А Material Copper Surface of the contact rail Untreated 408 Rail length mm Rail width mm 688 Busbar thickness mm 5

Clearance from back plate	mm	29
Mounting method		Other
Horizontal mounting		Yes
Vertical mounting		No
Insulated mounting		Yes
Max. tightening torque	Nm	0
Connection size, connection facility		Other