

**Main switch, 16 A, surface mounting, 3 pole, STOP function, Lockable in the 0 (Off) position, with push-through cable entry diaphragm., with assembly sheet screen**

**Part no. J16/B  
199728**

<b>General specifications</b>		
Product name		Eaton J-Range enclosed switch-disconnector
Part no.		J16/B
EAN		5027590551960
Product Length/Depth		115 millimetre
Product height		180 millimetre
Product width		100 millimetre
Product weight		0.527 kilogram
Certifications		IEC/EN 60204 VDE 0660 IEC/EN 60947-3 IEC/EN 60947
Product Tradename		J-Range
Product Type		Enclosed switch-disconnector
Product Sub Type		None
Catalog Notes		Rated Short-time Withstand Current (Icw) for a time of 1 second
<b>Features &amp; Functions</b>		
Features		Version as maintenance-/service switch Version as main switch
Fitted with:		Black rotary handle and locking ring Assembly sheet screen Push-through cable entry diaphragm
Functions		Interlockable STOP function
Locking facility		Lockable in the 0 (Off) position
Number of poles		Three-pole
<b>General information</b>		
Degree of protection		NEMA 12
Degree of protection (front side)		IP65
Lifespan, mechanical		300,000 Operations
Mounting method		Surface mounting
Mounting position		As required
Operating frequency		1200 Operations/h
Overvoltage category		III
Pollution degree		3
Product Category		Main switch
Rated impulse withstand voltage (Uimp)		6000 V AC
Safe isolation		440 V AC, Between the contacts, According to EN 61140
Safety parameter (EN ISO 13849-1)		B10d values as per EN ISO 13849-1, table C.1
Shock resistance		15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
Suitable for		Ground mounting
<b>Climatic environmental conditions</b>		
Ambient operating temperature (enclosed) - min		-25 °C
Ambient operating temperature (enclosed) - max		40 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Terminal capacities</b>		
Terminal capacity		1 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228 1 x (1.5 - 10) mm <sup>2</sup> , solid or stranded 2 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228 2 x (1.5 - 6) mm <sup>2</sup> , solid or stranded

Screw size	M4, Terminal screw
Tightening torque	1.6 Nm, Screw terminals
<b>Electrical rating</b>	
Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)	260 A
Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)	300 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)	290 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)	250 A
Rated operational current (Ie) at AC-21, 440 V	16 A
Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms	16 A
Rated operational power at AC-3, 380/400 V, 50 Hz	0 kW
Rated operational power at AC-23A, 400 V, 50 Hz	7 kW
Rated operational voltage (Ue) at AC - max	690 V
Rated uninterrupted current (Iu)	16 A
Uninterrupted current	Rated uninterrupted current Iu is specified for max. cross-section.
<b>Short-circuit rating</b>	
Rated conditional short-circuit current (Iq)	80 kA
Rated short-time withstand current (Icw)	0.64 kA 640 A, Contacts, 1 second
Short-circuit protection rating	50 A gG/gL, Fuse, Contacts
<b>Switching capacity</b>	
Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)	320 A
Voltage per contact pair in series	60 V
<b>Contacts</b>	
Number of auxiliary contacts (change-over contacts)	0
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	0
<b>Actuator</b>	
Actuator color	Black
Actuator type	Door coupling rotary drive
<b>Design verification</b>	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	UV resistance only in connection with protective shield.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Switch disconnecter (low voltage) (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ec@ss13-27-37-14-03 [AKF060018])			
Version as main switch			Yes
Version as maintenance-/service switch			Yes
Version as safety switch			No
Version as emergency stop installation			No
Version as reversing switch			No
Number of switches			1
Max. rated operation voltage Ue AC		V	690
Rated operating voltage		V	690 - 690
Rated permanent current Iu		A	16
Rated permanent current at AC-23, 400 V		A	
Rated permanent current at AC-21, 400 V		A	16
Rated operation power at AC-3, 400 V		kW	0
Rated short-time withstand current Icw		kA	0.64
Rated operation power at AC-23, 400 V		kW	7
Switching power at 400 V		kW	
Conditioned rated short-circuit current Iq		kA	80
Number of poles			3
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
Motor drive optional			No
Motor drive integrated			No
Voltage release optional			No
Device construction			Complete device in housing
Suitable for floor mounting			Yes
Suitable for front mounting 4-hole			No
Suitable for front mounting centre			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Colour control element			Black
Type of control element			Door coupling rotary drive
Interlockable			Yes
Type of electrical connection of main circuit			Screw connection
With pre-assembled cabling			No
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			12
Width		mm	100
Height		mm	180
Depth		mm	115
Width in number of modular spacings			