



Fuse-link, low voltage, 200 A, AC 660 V, 80 kA, BS88, 49 x 110 mm, gL/gG, BS, 92.5 mm fixing centres



Powering Business Worldwide™

Part no. **200A 660V INDUSTRIAL FUSE**
 Catalog No. **200N20**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	200
Rated voltage			AC 660 V
Construction size			BS88
Size			49 x 110 mm
Utilization category			gL/gG
Description			92.5 mm fixing centres
Breaking Capacity		kA	80
usable for size/applications			industrial
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88-2 IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	200
Rated voltage		V	660
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No