

Control transformer, 0.2 kVA, Rated input voltage 400± 5 % V, Rated output voltage 230 V



Powering Business Worldwide™

**Part no. STN0,2(400/230)
204977**

| General specifications | | |
|-------------------------------------|--|--|
| Product name | | Eaton Moeller® series STN Control transformer |
| Part no. | | STN0,2(400/230) |
| EAN | | 4015082049775 |
| Product Length/Depth | | 83 millimetre |
| Product height | | 112 millimetre |
| Product width | | 106 millimetre |
| Product weight | | 2.996 kilogram |
| Certifications | | VDE 0570 Part 2-2 UL Recognized IEC/EN 60204-1, ÖVE-EN 13 CSA-C22.2 No. 66 UL5085-1 VDE 0113, VDE 0100 Part 410 UL 5085-2 CSA-C22.2 No. 66.1-06 CE UL report applies to both US and Canada CSA-C22.2 No. 66.2-06 UL 506 UL File No.: E167225 Certified by UL for use in Canada UL Category Control No.: XPTQ2, XPTQ8 IEC/EN 61558-2-2 |
| Product Tradename | | STN |
| Product Type | | Control transformer |
| Product Sub Type | | None |
| Catalog Notes | | Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C |
| Features & Functions | | |
| Features | | Separate windings Fully Vacuum-impregnated |
| General information | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 40 °C |
| Connection lug | | Yes for > 115 A |
| Connection type | | Terminations, < 115 A |
| Degree of protection | | IP00 |
| Duty factor | | 100 % |
| Insulation class | | B |
| Primary tapping | | ± 5 % |
| Product category | | Single-phase control transformers ST |
| Suitable for | | Branch circuits, (UL/CSA) |
| Type | | Single-phase STN control transformers |
| Electrical rating | | |
| Efficiency | | 88 % |
| No-load losses | | 9 W |
| Rated frequency - min | | 50 Hz |
| Rated frequency - max | | 60 Hz |
| Rated power | | 0.2 V·A |
| Relative short-circuit voltage | | 6.8 % |
| Short-circuit losses | | 19 W |
| Short-time rating | | 0.38 kV·A |
| Voltage rating - max | | 600 V |

Design verification

| | | |
|--|--|--|
| Equipment heat dissipation, current-dependent P _{vid} | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 0 W |
| Rated operational current for specified heat dissipation (I _n) | | 0 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 28 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|---|-----------|
| Low-voltage industrial components (EG000017) / One-phase control transformer (EC002486) | | |
| Electric engineering, automation, process control engineering / Transformer, converter, coil / Control transformer / One-phase control transformer (ecl@ss13-27-03-13-02 [AAB620020]) | | |
| Built as safety transformer | | No |
| Built as isolating transformer | | No |
| Built as energy saving transformer | | No |
| Primary voltage 1 | V | 400 - 400 |
| Primary voltage 2 | V | 0 - 0 |
| Primary voltage 3 | V | 0 - 0 |
| Primary voltage 4 | V | 0 - 0 |
| Primary voltage 5 | V | 0 - 0 |
| Primary voltage 6 | V | 0 - 0 |
| Primary voltage 7 | V | 0 - 0 |
| Primary voltage 8 | V | 0 - 0 |
| Primary voltage 9 | V | 0 - 0 |
| Primary voltage 10 | V | 0 - 0 |
| Secondary voltage 1 | V | 230 - 230 |
| Secondary voltage 2 | V | 0 - 0 |
| Secondary voltage 3 | V | 0 - 0 |
| Secondary voltage 4 | V | 0 - 0 |
| Secondary voltage 5 | V | 0 - 0 |
| Secondary voltage 6 | V | 0 - 0 |
| Secondary voltage 7 | V | 0 - 0 |
| Secondary voltage 8 | V | 0 - 0 |
| Secondary voltage 9 | V | 0 - 0 |

| | | |
|---|----|--------|
| Secondary voltage 10 | V | 0 - 0 |
| Rated apparent power | VA | 200 |
| Power | W | |
| Power consumption in standby mode | W | 13 |
| Type of insulation material according to IEC 85 | | B |
| Short-circuit-proof | | No |
| Relative short circuit voltage | % | 6.8 |
| Width | mm | 106 |
| Height | mm | 112 |
| Depth | mm | 83 |
| Degree of protection (IP) | | IP00 |
| Ring core | | No |
| Suitable for mounting on PCB | | No |
| Modular version | | No |
| Conductor material | | Copper |