



Fuse-link, low voltage, 20 A, AC 500 V, 50 kA, D1, 13.2 x 6 mm, gL/gG, IEC, time-delay



Powering Business Worldwide™

Part no. FUZE-D1 20A T GL/GG 500VAC E16

Catalog No. 20D16

EL-Nummer (Norway) 1600294

Delivery program

| | | | |
|------------------------------|-------|----|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 20 |
| Rated voltage | | | AC 500 V |
| Construction size | | | D1 |
| Size | | | 13.2 x 6 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 50 |
| usable for size/applications | | | E16 for domestic and general industrial applications |
| Release characteristic | class | | time-delay |
| Standard/Approval | | | IEC |
| Shape | | | bottle |
| Standards/Regulations | | | IEC 60269-3 VDE 0636 |

Technical data ETIM 7.0

| | | | |
|---|--|---|---|
| Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015]) | | | |
| Construction size | | | D1 |
| Rated current | | A | 20 |
| Rated voltage | | V | 500 |
| Colour code | | | Blue |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Release characteristic | | | Time-lag |