

Label, emergency switching off, yellow, D=90mm, blank



**Part no.** M22-XAK  
**216464**  
**EL Number** 4355425  
**(Norway)**

| General specifications   |  |
|--|--|
| Product name   | Eaton Moeller® series M22 Accessory Emergency-Stop label           |
| Part no.   | M22-XAK  |
| EAN  | 4015082164645  |
| Product Length/Depth   | 90 millimetre  |
| Product height   | 1 millimetre   |
| Product width  | 90 millimetre  |
| Product weight   | 0.008 kilogram   |
| Compliances  | Contact Manufacturer   |
| Certifications   | UL/CSA certification not required<br>DNV<br>GL<br>LR               |
| Product Tradename  | M22  |
| Product Type   | Accessory  |
| Product Sub Type   | Emergency-Stop label   |
| Features & Functions   |  |
| Color  | Yellow   |
| Inscription  | None   |
| Language   | Other  |
| RAL-number   | 1004   |
| Shape  | Round  |
| General information  |  |
| Degree of protection   | IP66   |
| Size   | 90 x 90 mm   |
| Climatic environmental conditions  |  |
| Ambient operating temperature - min  | -25 °C   |
| Ambient operating temperature - max  | 70 °C  |
| Communication  |  |
| Connection to SmartWire-DT   | No   |
| Design verification  |  |
| Equipment heat dissipation, current-dependent P <sub>vid</sub>                   | 0 W  |
| Heat dissipation capacity P <sub>diss</sub>                                      | 0 W  |
| Heat dissipation per pole, current-dependent P <sub>vid</sub>                    | 0 W  |
| Rated operational current for specified heat dissipation (I <sub>n</sub> )       | 0 A  |
| Static heat dissipation, non-current-dependent P <sub>vs</sub>                   | 0 W  |
| 10.2.2 Corrosion resistance  | Meets the product standard's requirements.                         |
| 10.2.3.1 Verification of thermal stability of enclosures                         | Meets the product standard's requirements.                         |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       | Meets the product standard's requirements.                         |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.                         |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 | Please enquire   |
| 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact   | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions  | Meets the product standard's requirements.                         |
| 10.3 Degree of protection of assemblies  | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances   | Meets the product standard's requirements.                         |
| 10.5 Protection against electric shock   | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components                           | Does not apply, since the entire switchgear needs to be evaluated. |

|  |  |  |  |
|--|--|--|--|
| 10.7 Internal electrical circuits and connections        |  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors                 |  |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength                 |  |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage                         |  |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  |  | Not applicable.  |
| 10.11 Short-circuit rating                               |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility                      |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function                                |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 9.0

|  |  |    |        |
|--|--|----|--------|
| Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)   |  |    |        |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019]) |  |    |        |
| Literal imprint  |  |    | None   |
| Language of the imprint  |  |    | Other  |
| Imprint ISO symbols  |  |    | None   |
| Colour   |  |    | Yellow |
| Shape  |  |    | Round  |
| Width  |  | mm | 90     |
| Height   |  | mm | 1      |
| Outer diameter   |  | mm | 90     |