

**Illuminated pushbutton actuator, RMQ-Titan, Extended, maintained,
White, Blank, Bezel: titanium**



Part no. M22-DRLH-W

216788

EL Number

4355651

(Norway)

General specifications		
Product name		Eaton Moeller® series M22 Illuminated pushbutton actuator
Part no.		M22-DRLH-W
EAN		4015082167882
Product Length/Depth		30 millimetre
Product height		35 millimetre
Product width		30 millimetre
Product weight		0.013 kilogram
Compliances		Contact Manufacturer
Certifications		UL Category Control No.: NKCR CSA File No.: 012528 CSA Class No.: 3211-03 UL IEC/EN 60947 CSA VDE 0660 CSA-C22.2 No. 94-91 IEC/EN 60947-5 CE CSA-C22.2 No. 14-05 UL 508 UL File No.: E29184 GL DNV LR
Product Tradename		M22
Product Type		Illuminated pushbutton actuator
Product Sub Type		None
Features & Functions		
Bezel color		Titanium
Bezel material		Plastic
Color		White
Design		Extended Classical
Fitted with:		Front ring
Functions		Stay-put/spring-return function can be changed on device
Inscription		Blank
General information		
Degree of protection		IP67 NEMA 13 NEMA 4X NEMA 3R NEMA 12 IP69K IP66
Degree of protection (front side)		NEMA 4X IP67/IP69K
Lifespan, mechanical		1,000,000 Operations (AC operated)
Opening diameter		22.5 mm
Operating frequency		1800 Operations/h
Product category		RMQ-Titan
Size		Front diameter: 29.7 mm
Suitable for		Illumination
Type		Illuminated pushbutton actuator
Ambient conditions, mechanical		
Mounting position		As required

Shock resistance		30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Communication		
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuator		
Actuating force		5 N
Actuator color		White
Actuator function		Maintained Switching function latching
Contacts		
Force for positive opening - min		0 N
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss13-27-37-12-10 [AKF028019])		
Colour button		White
Number of command positions		1
Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0

Type of button			High
Suitable for illumination			Yes
With protective cover			No
Labelled			No
Switching function latching			Yes
Spring-return			No
With front ring			Yes
Material front ring			Plastic
Colour front ring			Titanium
Degree of protection (IP), front side			IP67/IP69K
Degree of protection (NEMA), front side			4X