

## Button plate, flat black, raised

Part no. **M22-XD-S-D17**  
**218192**

<b>General specifications</b>		
Product name		Eaton Moeller® series M22 Accessory Button plate
Part no.		M22-XD-S-D17
EAN		4015082181925
Product Length/Depth		24 millimetre
Product height		3 millimetre
Product width		24 millimetre
Product weight		0.002 kilogram
Certifications		UL/CSA certification not required
Product Tradename		M22
Product Type		Accessory
Product Sub Type		Button plate
<b>Features &amp; Functions</b>		
Color		Black
Design		Flush
Inscription		Individual inscription possible: > 5 characters: letter height 3 mm Individual inscription possible: ≤ 5 characters: letter height 5 mm RAISE
Inscription type		Text
Language		German
Shape		Round
<b>General information</b>		
Suitable for		Push button
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Legend plate for control circuit devices (EC000621)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Button plate for command and alarm devices (ecl@ss13-27-37-12-24 [AKF042019])

Shape		Round
Construction type		Flat
Colour		Black
Literal imprint		Raise
Language of the imprint		German
Imprint ISO symbols		None
Imprint		Other
Engravable		No
Programme diameter	mm	22
Width	mm	24
Height	mm	3
Outer diameter	mm	22.5
Suitable for push button		Yes
Suitable for illuminated push buttons		No
Suitable for indicator light		No
Suitable for mushroom head push button		No
Suitable for signalling lamp		No
Suitable for selector switch		No