



Fuse-link, LV, 224 A, AC 400 V, NH02, gL/gG, IEC, dual indicator, live gripping lugs

224NHG02B-400

Product name	Eaton Bussmann series low voltage NH Fuse
Part no.	224NHG02B-400
EAN	5027590468497
Product Length/Depth	135 millimetre
Product height	63 millimetre
Product width	40 millimetre
Product weight	407.333333 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-2 DIN 43620 IEC 60269-1
Product Tradename	None
Product Type	Low voltage NH fuse
Product Sub Type	None
Amperage Rating	224 A
Voltage rating	400 V
Voltage type	AC
Breaking capacity	120 kA
Class	Class gG/gL
Frequency rating - min	45 Hz
Frequency rating - max	62 Hz
Fuse size	NH02
Insulated metal gripping lugs (IMGL)	No
Suitable for	Microswitch BVL50

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH02
Voltage type		AC
Rated current	A	224
Rated voltage AC	V	400
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	12