



Fuse-link, low voltage, 224 A, AC 500 V, NH2, aM, IEC, dual indicator

224NHM2B

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		224NHM2B
EAN		5027590468688
Product Length/Depth		150 millimetre
Product height		71 millimetre
Product width		54 millimetre
Product weight		643 gram
Compliances		CE Marked RoHS Compliant
Certifications		DIN 43620 IEC 60269-1 IEC 60269-2
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Amperage Rating		224 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL
Fuse size		NH1
Insulated metal gripping lugs (IMGL)		No
Suitable for		SD1-D Single pole NH Fuse base TD1-D Tripe pole NH Fuse base Microswitch 170H0236 EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH2
Voltage type		AC
Rated current	A	224
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		aM (switchgear protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	15