

Miniature circuit breaker (MCB), 20 A, 3p, characteristic: D

Part no. PLSM-D20/3-MW
 242498
EL Number 1609254
(Norway)

| General specifications | | |
|---------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------|
| Product name | | Eaton Moeller series xPole - PLS6/M MCB |
| Part no. | | PLSM-D20/3-MW |
| EAN | | 4015082424985 |
| Product Length/Depth | | 80 millimetre |
| Product height | | 75 millimetre |
| Product width | | 52.5 millimetre |
| Product weight | | 0.314 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | xPole - PLS6/M |
| Product Type | | MCB |
| Product Sub Type | | None |
| Delivery program | | |
| Application | | Switchgear for residential and commercial applications xPole - Switchgear for residential and commercial applications |
| Number of poles | | Three-pole |
| Number of poles (total) | | 3 |
| Number of poles (protected) | | 3 |
| Tripping characteristic | | D |
| Release characteristic | | D |
| Amperage Rating | | 20 A |
| Type | | Miniature circuit breaker PLSM |
| Technical Data - Electrical | | |
| Voltage type | | AC |
| Rated operational voltage (Ue) - max | | 400 V |
| Rated insulation voltage (Ui) | | 440 V |
| Rated impulse withstand voltage (Uimp) | | 4 kV |
| Frequency rating - min | | 50 Hz |
| Frequency rating - max | | 60 Hz |
| Rated switching capacity (IEC/EN 60898-1) | | 10 kA |
| Rated short-circuit breaking capacity (EN 60898) at 230 V | | 10 kA |
| Rated short-circuit breaking capacity (EN 60898) at 400 V | | 10 kA |
| Rated short-circuit breaking capacity (IEC 60947-2) at 230 V | | 0 kA |
| Rated short-circuit breaking capacity (IEC 60947-2) at 400 V | | 0 kA |
| Overvoltage category | | III |
| Pollution degree | | 2 |
| Technical Data - Mechanical | | |
| Width in number of modular spacings | | 3 |
| Built-in depth | | 70.5 mm |
| Degree of protection | | IP20 |
| Connectable conductor cross section (solid-core) - min | | 1 mm ² |
| Connectable conductor cross section (solid-core) - max | | 25 mm ² |
| Connectable conductor cross section (multi-wired) - min | | 1 mm ² |
| Connectable conductor cross section (multi-wired) - max | | 25 mm ² |
| Design verification as per IEC/EN 61439 - technical data | | |
| Rated operational current for specified heat dissipation (In) | | 20 A |
| Heat dissipation per pole, current-dependent | | 0 W |

| | | |
|----------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------|
| Equipment heat dissipation, current-dependent | | 6.1 W |
| Static heat dissipation, non-current-dependent | | 0 W |
| Heat dissipation capacity | | 0 W |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 75 °C |
| Design verification as per IEC/EN 61439 | | |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| Additional information | | |
| Current limiting class | | 3 |
| Features | | Additional equipment possible |
| Special features | | Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity |
| Used with | | PLSM Miniature circuit breaker |

Technical data ETIM 9.0

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019]) | | |
| Built-in depth | mm | 70.5 |
| Release characteristic | | D |
| Number of poles (total) | | 3 |
| Number of protected poles | | 3 |
| Rated current | A | 20 |
| Rated voltage | V | 400 |
| Rated insulation voltage Ui | V | 440 |
| Rated impulse withstand voltage Uimp | kV | 4 |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V | kA | 10 |
| Voltage type | | AC |
| Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V | kA | 10 |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V | kA | 0 |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V | kA | 0 |
| Frequency | Hz | 50 - 60 |
| Power loss | W | 6.9 |

| | | | |
|-------------------------------------------------|--|-----------------|----------|
| Current limiting class | | | 3 |
| Flush-mounted installation | | | No |
| Concurrently switching neutral conductor | | | No |
| Over voltage category | | | 3 |
| Pollution degree | | | 2 |
| Additional equipment possible | | | Yes |
| Width in number of modular spacings | | | 3 |
| Degree of protection (IP) | | | IP20 |
| Ambient temperature during operating | | °C | -25 - 75 |
| Connectable conductor cross section multi-wired | | mm ² | 1 - 25 |
| Connectable conductor cross section solid-core | | mm ² | 1 - 25 |
| Explosion-proof | | | No |