



Remote testing module, max. 400V-AC, 0.5A, 0.5HP

**Part no.** Z-FW/050  
**Catalog No.** 248301  
**Alternate Catalog No.** Z-FW/050

Similar to illustration

## Delivery program

Basic function			Accessories for residual current circuit-breakers
Basic function accessories			Remote test module
Application			Switchgear for industrial and advanced commercial applications
Rated fault current	$I_{\Delta N}$	A	0.5
Product range			Accessory
Side mounting			for fitting on left to: FI

## Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0.02
Equipment heat dissipation, current-dependent	$P_{vid}$	W	0.02
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

## Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Earth leakage switch
Additional equipment			Monitoring unit
Attached at delivery			No
Assembly width (TE)			0.5
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	0
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0

## Dimensions

