



Fuse-link, low voltage, 250 A, AC 500 V, NH2, aM, IEC, dual indicator

250NHM2B

Product name	Eaton Bussmann series low voltage NH Fuse
Part no.	NH FUSE 250A 500V aM SIZE 2 DUAL IND
EAN	5027590469814
Product Length/Depth	150 millimetre
Product height	71 millimetre
Product width	54 millimetre
Product weight	659 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-1 IEC 60269-2 DIN 43620
Product Tradename	None
Product Type	Low voltage NH fuse
Product Sub Type	None
Amperage Rating	250 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Class	Class aM
Fuse size	NH2
Insulated metal gripping lugs (IMGL)	No
Suitable for	SD2-D Single pole NH Fuse base TD2-D Tripe pole NH Fuse base Microswitch 170H0235 Microswitch 170H0236 EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH2
Voltage type		AC
Rated current	A	250
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		aM (switchgear protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	17