

Low voltage British standard fuse



250P11C

Similar to illustration

Product name Part no. EAN Product Length/Depth Product width Product width Product Tradename Product Tradename Product Type Product Sub Type Amperage Rating Voltage rating Voltage type Breaking capacity Class Class gG/gL Eaton Bussmann series low voltage British standard fuse 250P11C 250P1C 250P		
Part no. EAN Product Length/Depth Product height Product weight Compliances Product Tradename Product Type Product Sub Type Amperage Rating Voltage rating Voltage type Braking capacity Part no. 250P11C 50027590039444 210 millimetre 201 m	Product name	Faton Duramana agrica lauvualtara Dritish atandard from
EAN Product Length/Depth Product height Product width Product weight Product weight Product weight Product weight Product Tradename Product Tradename Product Type Product Sub Type Amperage Rating Voltage rating Voltage type Feaking capacity Page 1		·
Product Length/Depth Product height Product height Product width Product weight Compliances Product Tradename Product Type Product Sub Type Amperage Rating Voltage rating Voltage type Product Length/Depth Product Length/Depth Product Length/Depth Product Weight Product Weight Product Weight Product Weight Product Type Product Type Product Sub T	Part no.	250P11C
Product height59 millimetreProduct width59 millimetreProduct weight657 gramCompliancesRoHS CompliantProduct TradenameNoneProduct TypeLow voltage British standard fuseProduct Sub TypeNoneAmperage Rating250 AVoltage type600 VVoltage typeAC/DCBreaking capacity200 kA	EAN	5027590039444
Product width Product weight Compliances RoHS Compliant Product Tradename Product Trype Rough Sub Type Rough Su	Product Length/Depth	210 millimetre
Product weight Compliances Product Tradename Product Type Product Sub Type None Product Sub Type None Amperage Rating Voltage type Voltage type Breaking capacity AC/DC Breaking capacity 657 gram ROHS Compliant ROHS Compliant Low voltage British standard fuse Low	Product height	59 millimetre
CompliancesRoHS CompliantProduct TradenameNoneProduct TypeLow voltage British standard fuseProduct Sub TypeNoneAmperage Rating250 AVoltage rating600 VVoltage typeAC/DCBreaking capacity200 kA	Product width	59 millimetre
Product TradenameNoneProduct TypeLow voltage British standard fuseProduct Sub TypeNoneAmperage Rating250 AVoltage rating600 VVoltage typeAC/DCBreaking capacity200 kA	Product weight	657 gram
Product Type Product Sub Type None Amperage Rating Voltage rating Voltage type Breaking capacity Low voltage British standard fuse None Amount None 600 V 250 A 600 V 200 kA	Compliances	RoHS Compliant
Product Sub TypeNoneAmperage Rating250 AVoltage rating600 VVoltage typeAC/DCBreaking capacity200 kA	Product Tradename	None
Amperage Rating 250 A Voltage rating 600 V Voltage type AC/DC Breaking capacity 200 kA	Product Type	Low voltage British standard fuse
Voltage rating600 VVoltage typeAC/DCBreaking capacity200 kA	Product Sub Type	None
Voltage rating600 VVoltage typeAC/DCBreaking capacity200 kA		
Voltage type AC/DC Breaking capacity 200 kA	Amperage Rating	250 A
Breaking capacity 200 kA	Voltage rating	600 V
	Voltage type	AC/DC
Class gG/gL	Breaking capacity	200 kA
	Class	Class gG/gL
Connection Blade end	Connection	Blade end

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrica	l installation, device / Safety fu	use inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	600
Rated voltage DC	V	250
Rated current	A	250
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		
Centre-to-centre distance of connections	mm	