



Fuse-link, low voltage, 25 A, AC 600 V, DC 250 V, 200 kA, HRCI-CA, 14 x 55 mm, CSA



Part no. **25A 600V BRUSH FUSE CANADA**
 Catalog No. **25CIF21**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	25
Rated voltage			AC 600 V DC 250 V
Construction size			HRCI-CA
Size			14 x 55 mm
Breaking Capacity		kA	200
usable for size/applications			Overload and short-circuit protection
Standard/Approval			CSA
Shape			offset bolted tags
Standards/Regulations			CSA C22.2 No. 106-M92
Optional accessories			fuse-holder CM32FC

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (eci@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	25
Rated voltage		V	600
Voltage type			AC/DC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_4127_CIF21.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/iec_british0/hrci_industrial_ceramicbody/cif21_hrci-ca.html