



Fuse-link, LV, 25 A, AC 660 V, DC 250 V, BS88/A2, 22 x 82 mm, gL/gG, BS

25H07-660

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse	
Part no.	25H07-660	
EAN	5027590470186	
Product Length/Depth	84.5 millimetre	
Product height	21 millimetre	
Product width	21 millimetre	
Product weight	48.75 gram	
Compliances	Contact Manufacturer	
Product Tradename	None	
Product Type	Low voltage British standard fuse	
Product Sub Type	None	
Amperage Rating	25 A	
Voltage rating	690 V	
Voltage type	AC/DC	
Breaking capacity	80 kA	
Class	Class gG/gL	
Application	general industrial applications	
Fuse type	H07-660	
Fuse size	BS88/A2	
Fitted with:	Offset bolted tags	
Connection	Bolt-on	

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A2
Type of current		AC/DC
Rated voltage AC	V	690
Rated voltage DC	V	460
Rated current	A	25
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	3.1
Mounting holes		M5
Centre-to-centre distance of connections	mm	71.5