



Fuse-link, low voltage, 25 A, AC 400 V, 120 kA, NH000, gFF, IEC, dual indicator, insulated gripping lugs



Part no. **25Amp 400V AC GFF 000 NH FUSE**
 Catalog No. **25NHFF000BI-400**

Delivery program

Product range			Fuse
Field of application			low voltage
Rated current	I	A	25
Rated voltage			AC 400 V
Construction size			NH000
Utilization category			gFF
Status indicator			dual indicator
Description			insulated gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square-body with knife blade contacts
Standards/Regulations			IEC 60269-1
Optional accessories			fuse-holder SD00-D and SD00-S

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	25
Equipment heat dissipation, current-dependent	P_{vid}	W	2.3

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH000
Rated current		A	25
Rated voltage		V	400
Voltage type			
Rated switching capacity		kA	120
Utilization category			Other
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No