



Fuse-link, LV, 25 A, AC 500 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs



25NHG000BI

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		NH FUSE 25A 500V SIZE 000 GG IMGL
EAN		5027590470988
Product Length/Depth		79 millimetre
Product height		51 millimetre
Product width		21 millimetre
Product weight		135 gram
Compliances		CE Marked RoHS Compliant
Certifications		DIN 43620 IEC 60269-2 IEC 60269-1
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Amperage Rating		25 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL
Fuse size		NH000
Insulated metal gripping lugs (IMGL)		Yes
Suitable for		Microswitch 170H0236 EBF Vertical fuse rail EBV Vertical fuse switch-disconnectors EBH Size 000 Horizontal fuse switch-disconnectors

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH000
Voltage type		AC
Rated current	A	25
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		Yes
Power loss at rated current	W	3.1