



Fuse-link, low voltage, 25 A, AC 400 V, 50 kA, D02, gR, IEC, ultra rapid



Part no. **FUSE-D02 25A GR 400VAC E18**
 Catalog No. **25NZ02R**

Similar to illustration

Delivery program

| | | | |
|------------------------------|-------|----|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 25 |
| Rated voltage | | | AC 400 V |
| Construction size | | | D02 |
| Utilization category | | | gR |
| Breaking Capacity | | kA | 50 |
| usable for size/applications | | | E18 for domestic and general industrial applications |
| Release characteristic | class | | ultra rapid |
| Standard/Approval | | | IEC |
| Shape | | | bottle |
| Standards/Regulations | | | IEC 60269-3 VDE 0636 |

Technical data ETIM 7.0

| | | | |
|---|--|---|---|
| Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011]) | | | |
| Construction size | | | D02 |
| Rated current | | A | 25 |
| Rated voltage | | V | 400 |
| Colour code | | | Yellow |
| Utilization category | | | gR (general purpose semiconductor protection) |