

Main switch assembly kit, on the left side, red, size 2



**Part no.**                      **NZM2-XSRM-L**  
**266672**

<b>General specifications</b>		
Product name		Eaton Moeller series NZM operating element
Part no.		NZM2-XSRM-L
EAN		4015082666729
Product Length/Depth		190 millimetre
Product height		220 millimetre
Product width		190 millimetre
Product weight		2.024 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		UL (Category Control Number DIHS) UL listed UL489 CE marking CSA certified UL (File No. E140305) IEC60947 CSA (Class No. 1437-01) CSA (File No. 22086) CSA-C22.2 No. 5-09
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element
<b>Delivery program</b>		
Type		Accessory Main switch assembly kit for side panel mounting
Features		Lockable For direct mounting of circuit-breaker and handle in the side wall of the control cabinet Red-yellow for emergency switching off
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch
Frame		NZM2
Fitted with:		External warning plate/markings plate in German/English Special short extension shaft Black and yellow lightning symbol Extension shaft Mounting brackets Door coupling rotary handle Padlock
Suitable for		Switch disconnecter Emergency stop Power circuit breaker
Used with		N(S)2(-4) PN2(-4) NZM2(-4)
<b>Technical Data - Mechanical</b>		
Color		Red
Cover/door type		Door interlock extension cannot be used. Door interlock lockable in 0 position on handle Narrowest minimum clearance between enclosure side plates of control panel and circuit breaker is defined by mounting bracket.
Degree of protection / NEMA enclosure type		IP66 4X. 12
Activation type		Actuation on the left
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch
<b>Design verification as per IEC/EN 61439</b>		

10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage		No
With key lock		No
Padlock locking		Yes
Colour		Red
Suitable for emergency stop		Yes
With extension shaft		Yes
Suitable for power circuit breaker		Yes
Suitable for switch disconnecter		Yes
Degree of protection (NEMA)		4X, 12