

Fuse-link with blink application, D02, 35A, 400 V, gL/gG, set consists of 3 pcs.



Part no. Z-SLS/B-35A
268991

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-SLS/B-35A
EAN		4015082689919
Product Length/Depth		45 millimetre
Product height		80 millimetre
Product width		54 millimetre
Product weight		0.145 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Ambient operating temperature - max		55 °C
Ambient operating temperature - min		-25 °C
Amperage Rating		35 A
Color		Black
Equipment heat dissipation, current-dependent		2.8 W
Frame		D02
Functions		Accessory
Heat dissipation capacity		0 W
Heat dissipation per pole, current-dependent		0 W
Rated operational current for specified heat dissipation (I _n)		35 A
Rated operational voltage (U _e) - max		400 V
Rated uninterrupted current (I _u)		35 A
Special features		With flashing function Snap-fit on DIN rail 1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator
Static heat dissipation, non-current-dependent		0 W
Test voltage		5 kV
Type		Accessory Fuse material Fuse set
Used with		Z-SLS/CEK Z-SLS/NEOZ Z-SLK/NEOZ Fuse links Accessory Fuse material Fuse set
Utilization category		gL/gG (cable protection/equipment protection) gG (gL)
Voltage rating		60 V AC - 400 V AC
Voltage rating at AC		50 - 400 V AC
Voltage rating at DC		50 - 250 V DC

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss13-27-14-21-19 [ACN353016])

Construction size		D02
Rated current	A	35
Rated voltage	V	400
Colour code		Black
Utilization category		gG (cable protection/equipment protection)