



Busbar, isolated, 63A, 3p, 3Mod



Powering Business Worldwide™

Part no. Z-GV-10/3P-3TE
Catalog No. 271060

Similar to illustration

Technical data ETIM 7.0

| | | | |
|--|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011]) | | | |
| Number of phases | | | 3 |
| Number of poles | | | 3 |
| Suitable for number of devices | | | 0 |
| Pitch dimensions | | mm | 0 |
| Cross section | | mm ² | 10 |
| Length | | mm | 1000 |
| Number of modular spacings | | | 3 |
| Rated permanent current I _u | | A | 63 |
| Type of electric connection | | | Fork |
| Insulated | | | Yes |
| Rated surge voltage | | kV | 4 |
| Conditioned rated short-circuit current I _q | | kA | 0 |
| Max. rated operation voltage U _e | | V | 500 |
| Rated short-time withstand current I _{cw} | | kA | 0 |
| Suitable for devices with N-busbar | | | No |
| Suitable for devices with auxiliary switch | | | No |