DATASHEET - Z-UDL24



Twin light, 24AC/DC, red/green

Part no. Z-UDL24 Catalog No. 284928



Similar to illustration

Design verification as per IEC/EN 61439

Technical data for design verification			
Equipment heat dissipation, current-dependent	P_{vid}	W	2

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Indicator light for distribution board (EC001657)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Indicator light for distribution board (ecl@ss10.0.1-27-14-23-24 [ACN367011])

Colour calotte Lamp type Lamp socket Max. lamp power Rated voltage Voltage type Width in number of modular spacings Dither LED Under V 24 AC/DC Width in number of modular spacings Ruilt-in depth					
Lamp socket Max. lamp power Rated voltage V 24 Voltage type Width in number of modular spacings Other AC/DC Under type AC/DC	Colour calotte	Other			
Max. lamp power Rated voltage V 24 Voltage type AC/DC Width in number of modular spacings 1	Lamp type	LED			
Rated voltage V 24 Voltage type AC/DC Width in number of modular spacings 1	Lamp socket	Other			
Voltage type AC/DC Width in number of modular spacings 1	Max. lamp power	W 2			
Width in number of modular spacings	Rated voltage	V 24			
	Voltage type	AC/DC			
Built-in depth mm 60	Width in number of modular spacings	1			
	Built-in depth	mm 60			
Degree of protection (IP)	Degree of protection (IP)	IP40			