

Fuse-link, D02, 20A, 400 V, gL/gG



**Part no.**                    **Z-D02/SE-20**  
**288940**

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-D02/SE-20
EAN		4015082889401
Product Length/Depth		36 millimetre
Product height		16 millimetre
Product width		16 millimetre
Product weight		0.012 kilogram
Compliances		RoHS conform
Certifications		DIN 49522 DIN VDE 0636
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Ambient operating temperature - max		55 °C
Ambient operating temperature - min		-25 °C
Amperage Rating		20 A
Color		Blue
Equipment heat dissipation, current-dependent		1.8 W
Frame		D02
Functions		Accessory
Fuse cartridge		D02
Heat dissipation capacity		0 W
Heat dissipation per pole, current-dependent		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		20 A
Rated operational voltage (U <sub>e</sub> ) - max		400 V
Rated uninterrupted current (I <sub>u</sub> )		20 A
Special features		Snap-fit on DIN rail in a plastic box in the colour of the indicator
Static heat dissipation, non-current-dependent		0 W
Type		Accessory Fuse links Fuse material
Used with		Fuse links Accessory Fuse material
Utilization category		gL/gG (cable protection/equipment protection) gG (gL)
Voltage rating		400 V AC
Voltage rating at DC		220 V DC

**Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss13-27-14-21-19 [ACN353016])		
Construction size		D02
Rated current	A	20
Rated voltage	V	400

Colour code		Blue
Utilization category		gG (cable protection/equipment protection)