



**Door white**

**Part no.** BP-DS-600/4-W  
**Catalog No.** 292440

**EL-Nummer (Norway)** 0002456139

### Delivery program

|                      |  |    |                       |
|----------------------|--|----|-----------------------|
| Mounting type        |  |    | Surface mounted       |
| Material             |  |    | Sheet steel           |
| Door interlock       |  |    | Three-point turn-lock |
| Degree of Protection |  |    | IP30                  |
| Surface finish       |  |    | With powder coating   |
| Width                |  | mm | 600                   |
| Height               |  | mm | 460                   |
| Suitable for height  |  | mm | 460                   |
| Suitable for width   |  | mm | 600                   |
| Colour               |  |    | white (RAL 9016)      |

### Technical data ETIM 7.0

|   |  |    |                |
|---|--|----|----------------|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)  |  |    |                |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecI@ss10.0.1-27-18-22-04 [ACN614011]) |  |    |                |
| Model   |  |    | Stop door      |
| Version as glazed door  |  |    | No             |
| Version as door for disconnecting switch interlocking   |  |    | No             |
| Width   |  | mm | 615            |
| Height  |  | mm | 410            |
| Depth   |  | mm | 45             |
| EMC-version   |  |    | No             |
| Material  |  |    | Steel          |
| Surface finishing   |  |    | Powder coating |
| Colour  |  |    | White          |
| Degree of protection (IP)   |  |    | IP30           |
| Degree of protection (NEMA)   |  |    |                |