



Fuse-link, LV, 32 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs

**32NHG000BI-690**

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		NH FUSE 32A 690V SIZE 000 GG IMGL
EAN		5027590476867
Product Length/Depth		79 millimetre
Product height		51 millimetre
Product width		21 millimetre
Product weight		131 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-1 IEC 60269-2 DIN 43620
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Amperage Rating		32 A
Voltage rating		690 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL
Fuse size		NH000
Insulated metal gripping lugs (IMGL)		Yes
Suitable for		Microswitch 170H0236 EBF Vertical fuse rail EBV Vertical fuse switch-disconnectors EBH Size 000 Horizontal fuse switch-disconnectors

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH000
Voltage type		AC
Rated current	A	32
Rated voltage AC	V	690
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		Yes
Power loss at rated current	W	305