



Fuse-link, low voltage, 32 A, AC 500 V, NH000, aM, IEC, dual indicator

**32NHM000B**

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		NH FUSE 32A 500V aM SIZE 000 DUAL IND
EAN		5027590476942
Product Length/Depth		125 millimetre
Product height		58 millimetre
Product width		30 millimetre
Product weight		190 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-2 IEC 60269-1 DIN 43620
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Amperage Rating		32 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class aM
Fuse size		NH000
Insulated metal gripping lugs (IMGL)		No
Suitable for		Microswitch 170H0236 EBF Vertical fuse rail EBV Vertical fuse switch-disconnectors EBH Size 000 Horizontal fuse switch-disconnectors

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH000
Voltage type		AC
Rated current	A	32
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		aM (switchgear protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	2.1