



**EATON 3S 700 DIN**

**Part no.  
Catalog No.**

**EATON 3S 700 DIN  
3S700DIN**

**Technical data ETIM 7.0**

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ec@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	161 - 184
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	230 - 230
Secondary frequency	Hz	50 - 60
Output effective power	W	420
Output apparent power	VA	700
Type of interface		USB
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	86
Width	mm	170
Depth	mm	335
Transition time for full load	min	2
Weight	kg	3.8
Network-management		No
USV- technology		Offline
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	97
Efficiency in eco-mode	%	97
Potential free switch contact		No
Auto shut down function		Yes
Input connection		Protective contact (SCHUKO)
Number of output connections C13		0
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		6
Number of output connections fixed connection		0