



Fuse-link, low voltage, 400 A, AC 600 V, DC 250 V, HRC Form II, 73 x 210 mm, gL/gG, CSA, Current-limiting

400P11C

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	400P11C
EAN	5027590047043
Product Length/Depth	210 millimetre
Product height	59 millimetre
Product width	59 millimetre
Product weight	657 gram
Compliances	RoHS Compliant
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	400 A
Voltage rating	600 V
Voltage type	AC/DC
Breaking capacity	200 kA
Class	Class gG/gL
Application	general industrial applications
Connection	Bolt-on

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	600
Rated voltage DC	V	250
Rated current	A	400
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M10
Centre-to-centre distance of connections	mm	186