

Fuse-link, low voltage, 40 A, DC 500 V, BS88/A3, 26 x 86 mm, BS



40KS07

roduct name	Eaton Bussmann series low voltage British standard fuse
art no.	40KS07
AN	5027590480147
Product Length/Depth	86 millimetre
Product height	27 millimetre
Product width	27 millimetre
Product weight	0.001 gram
Compliances	RoHS Compliant CE Marked
ertifications	IEC 60269 EAC BS88
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	40 A
oltage rating	500 V
oltage type	DC
Breaking capacity	40 kA
llass	Class gG/gL
pplication	general industrial applications
use type	KS07
use size	BS88/A3
Connection	Bolt-on

Technical data ETIM 8.0

1001111041 4444 211111 010		
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, do	evice / Safety fuse ir	serts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269		A3
Type of current		DC
Rated voltage AC	V	
Rated voltage DC	V	500
Rated current	Α	40
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	40
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M5
Centre-to-centre distance of connections	mm	71.5