

Fuse-link, LV, 4 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs



EL Number
(Norway)

4NHG000B-690
1664096

Similar to illustration

Product name	Eaton Bussmann series low voltage NH Fuse
Part no.	NH FUSE 4A 690V SIZE 000 GG MGL
EAN	5027590482394
Product Length/Depth	79 millimetre
Product height	51 millimetre
Product width	21 millimetre
Product weight	131 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-1 IEC 60269-2 DIN 43620
Product Tradename	None
Product Type	Low voltage NH fuse
Product Sub Type	None
Amperage Rating	4 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	120 kA
Class	Class gG/gL
Frequency rating - min	45 Hz
Frequency rating - max	62 Hz
Fuse size	NH000
Insulated metal gripping lugs (IMGL)	No
Suitable for	Microswitch 170H0236 EBF Vertical fuse rail EBV Vertical fuse switch-disconnectors EBH Size 000 Horizontal fuse switch-disconnectors

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH000
Voltage type		AC
Rated current	A	4
Rated voltage AC	V	690
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	2

