



Low voltage NH fuse

500NHFF3BI-400

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		500NHFF3BI-400
EAN		5027590482721
Product Length/Depth		150 millimetre
Product height		86 millimetre
Product width		71 millimetre
Product weight		904 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC 60269-1 IEC 60269-2 DIN 43620
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Amperage Rating		500 A
Voltage rating		400 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gFF
Frequency rating - min		45 Hz
Frequency rating - max		62 Hz
Fuse size		NH3
Insulated metal gripping lugs (IMGL)		Yes
Suitable for		SD3-D Single pole NH Fuse base TD3-D Tripe pole NH Fuse base

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH3
Voltage type		AC
Rated current	A	500
Rated voltage AC	V	400
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		Yes
Power loss at rated current	W	47