



Fuse-link, low voltage, 50 A, AC 600 V, DC 250 V, 200 kA, HRCII-C, 22 x 87 mm, CSA

Part no. 50A 600V CANADIAN FUSE
Catalog No. 50K07C

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	50
Rated voltage			AC 600 V DC 250 V
Construction size			HRCII-C
Size			22 x 87 mm
Breaking Capacity		kA	200
usable for size/applications			Cable protection
Standard/Approval			CSA
Shape			offset bolted tags
Standards/Regulations			CSA C22.2 No. 106-M1992

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	50
Rated voltage		V	600
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/iec_british0/hrc_form_ii_current-limitingfuses1.html
-------------------------	---