



Fuse-link, low voltage, 560 A, AC 660 V, BS88, 74 x 112 mm, gL/gG, BS

560R20

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		560R20
EAN		5027590049856
Product Length/Depth		112 millimetre
Product height		75 millimetre
Product width		75 millimetre
Product weight		942 gram
Compliances		RoHS Compliant CE Marked
Certifications		BS88 IEC 60269 EAC
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		560 A
Voltage rating		660 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		R20
Connection		94 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC
Rated voltage AC	V	660
Rated voltage DC	V	
Rated current	A	560
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	43
Mounting holes		M8
Centre-to-centre distance of connections	mm	94