



Eaton Protection Station 650 USB DIN

Part no. Eaton Protection Station 650 USB DIN
Catalog No. 61062

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ec@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	160 - 284
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	230 - 230
Secondary frequency	Hz	50 - 60
Output effective power	W	400
Output apparent power	VA	650
Type of interface		USB
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	327
Width	mm	185
Depth	mm	149
Transition time for full load	min	1.5
Weight	kg	3.8
Network-management		No
USV- technology		Offline
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	97
Efficiency in eco-mode	%	97
Potential free switch contact		No
Auto shut down function		Yes
Input connection		Protective contact (SCHUKO)
Number of output connections C13		0
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		8
Number of output connections fixed connection		0