



Fuse-link, low voltage, 6 A, AC 500 V, 50 kA, D1, 13.2 x 6 mm, gR, IEC, fast-acting

**Part no.** FUSE 6A DI/E16 500VAC DZ  
**Catalog No.** 6D16Q

**EL-Nummer (Norway)** 1601278

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	6
Rated voltage			AC 500 V
Construction size			D1
Size			13.2 x 6 mm
Utilization category			gR
Breaking Capacity		kA	50
usable for size/applications			E16
Release characteristic	class		fast-acting
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])			
Construction size			D1
Rated current		A	6
Rated voltage		V	500
Colour code			Green
Utilization category			gR (general purpose semiconductor protection)
Release characteristic			Fast (F)