



Fuse-link, low voltage, 800 A, AC 690 V, 120 kA, NH4, gL/gG, IEC, single indicator, live gripping lugs



**Part no.** NH FUSE 800A 690V GG/GL SIZE 4  
**Catalog No.** 800NHG4B-690

**EL-Nummer (Norway)** 1664133

**Delivery program**

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	800
Rated voltage			AC 690 V
Construction size			NH4
Utilization category			gL/gG
Status indicator			single indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with slotted blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

**Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH4
Rated current		A	800
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No